

Road holding, safety and quality

- Rear doors or ramp**
 Brenderup Cargoliner is available with rear doors or a ramp. Light goods can be taken up the ramp. Rear doors, on the other hand, are easier to open and require less space.
- Maximise road holding**
 Brenderups have an A-frame drawbar, which, together with the rigid chassis, independent wheel suspension with rubber torsion axles, quality tyres and rims, provides the best ride.
- Long service life**
 All the individual chassis components are galvanised and so have maximum protection against rust. The chassis is bolted or riveted together, making it possible to replace individual components in the event of a collision.
- Low loading height**
 Cargoliners from Brenderup have their wheels on the side, which means one of the lowest loading heights on the market, while the low centre of gravity ensures optimum road-holding.
- Safety**
 Brenderup trailers are equipped with recessed lights and cables/sockets of the highest quality, as well as a direct earth connection to the vehicle's electrical system.
- Reliable supply of spare parts**
 Thule Trailers A/S has comprehensive spare parts documentation for its trailers. Contact your Brenderup dealer, who will always be happy to help with advice, guidance and servicing.



Cargoliner



Cargo 2205/2260 with lid:

Cargo 2205/2260 is a closed trailer, equipped with alu-/wooden lid. Available with doors or ramp - equipped with much standard equipment, a.o. jockey wheel and ground support. A lot of smart and practical details such as:

- The lid can be opened and locked.
- The doors can be opened to 225 degrees wide and fixed to the side.
- The ground support is positioned under the platform.
- The ramp is equipped with an extension which unfolds when the ramp is let down.



^{*)} Payload for models with doors/ramp.

Cargo 2205 Technical data

Total weight	750	1000	kg
Payload*	472/453	693/674	kg
Int. length	205	205	cm
Int. width	131	131	cm
Int. height	111	111	cm
Wheels	R 13"	R 13"	



^{*)} Payload for models with doors/ramp.

Cargo 2260 Technical data

Total weight	750	1000	1300	kg
Payload*	407/392	600/585	886/871	kg
Int. length	260	260	260	cm
Int. width	131	131	131	cm
Int. height	131	131	131	cm
Wheels	R 13"	R 13"	R 13"	

Model	Doors/Ramp/Lid	Box int. dimensions LxWxH cm	Internal door - dim. WxH cm	Overall length cm	Overall width cm	Overall height cm	Load. height cm	Gross weight kgs	Pay load kgs	Brakes	No. of axles	Tyres	Side door	Sidepouced hatch	Internal light	Propstands
-------	----------------	------------------------------	-----------------------------	-------------------	------------------	-------------------	-----------------	------------------	--------------	--------	--------------	-------	-----------	------------------	----------------	------------

Cargoliner - technical data

Cargoliner - technical data																	Accessories																
Cargo 2205	Rear doors/Ramp	205x131x111	-	322	175	164	54	750	472/453	-	1	R13"	-	-	-	-																	
Cargo 2205	Rear doors/Ramp	205x131x111	-	346	179	164	54	1000	693/674	+	1	R13"	-	-	-	-																	
Cargo 2260	Rear doors/Ramp	260x131x131	-	378	175	164	55	750	407/392	-	1	R13"	-	-	-	-																	
Cargo 2260	Rear doors/Ramp	260x131x131	-	404	179	164	53	1000	600/585	+	1	R13"	-	-	-	-																	
Cargo 2260	Rear doors/Ramp	260x131x131	-	404	179	164	54	1300	886/871	+	1	R14"	-	-	-	-																	
7205 B	Rear doors/Ramp	205x128x150	120x145	350	179	205	54	1000	635/624	+	1	R13"	+	-	+	+																	
7205 B	Rear doors/Ramp	205x128x150	120x145	350	179	205	54	1300	929/918	+	1	R14"	+	-	+	+																	
7260 B	Rear doors/Ramp	260x128x150	120x145	405	179	205	54	1000	592/586	+	1	R14"	+	-	+	+																	
7260 B	Rear doors/Ramp	260x128x150	120x145	405	179	205	54	1300	868/862	+	1	R14"	+	-	+	+																	
7260 B	Rear doors/Ramp	260x128x185	120x180	405	179	240	54	1000	559/549	+	1	R13"	+	+	+	+																	
7260 B	Rear doors/Ramp	260x128x185	120x180	405	179	240	54	1300	835/825	+	1	R14"	+	+	+	+																	
7260 B	Rear doors/Ramp	260x153x150	145x145	405	204	205	54	1000	545/532	+	1	R13"	+	-	+	+																	
7260 B	Rear doors/Ramp	260x153x150	145x145	405	204	205	54	1300	843/830	+	1	R14"	+	-	+	+																	
7260 B	Rear doors/Ramp	260x153x185	145x180	405	204	240	54	1300	811/793	+	1	R14"	+	+	+	+																	
7260 B	Rear doors/Ramp	260x153x185	145x180	405	204	240	54	1500	1011/993	+	1	R14"	+	+	+	+																	
7260 B	Rear doors/Ramp	260x153x185	145x180	405	204	240	54	1600	1007/989	+	1	R14"	+	+	Standard	+																	
7260 TB	Rear doors/Ramp	260x153x185	145x180	405	204	240	54	2000	1407/1389	+	2	R13"	+	+	Standard	+																	
7260 TB	Rear doors/Ramp	260x153x220	145x215	405	204	275	54	2000	1367/1349	+	2	R13"	+	+	Standard	+																	
7300 TB	Rear doors/Ramp	300x153x185	145x180	444	204	240	54	2000	1377/1359	+	2	R13"	+	+	Standard	+																	
7300 TB	Rear doors/Ramp	300x153x185	145x180	444	204	240	54	2500	1823/1805	+	2	R14"	+	+	Standard	+																	
7300 TB	Rear doors/Ramp	300x153x220	145x215	444	204	275	54	2500	1779/1761	+	2	R14"	+	+	Standard	+																	
7350 TB	Rear doors/Ramp	350x153x185	145x180	494	204	240	54	2500	1803/1785	+	2	R14"	+	+	Standard	+																	
7350 TB	Rear doors/Ramp	350x153x220	145x215	494	204	240	54	2500	1755/1737	+	2	R14"	+	+	Standard	+																	

Note for accessories: *) Sidemounted hatch is available in two sizes, 244x147 cm or 287x147 cm. Sidemounted hatch is not available for models 7205 or 7260 with 150 cm's internal height. Max loading of ramps: Sacktruck 250 kg, motorcycle 300 kg.

The 7000 series is made in three different versions:



Reardoors



Ramp



Sidemounted hatch

Dealer:



Thule Trailers A/S, Fabriksvej 4, DK-5580 Nr. Aaby
 Tél. (+45) 63 42 22 00, fax (+45) 63 42 22 75.
www.brenderup.com

We reserve the right to introduce construction changes without prior notice. We accept no liability for printing errors.

See the following Special Brochures for our wide range of Brenderup trailers:

- Leisure trailers
- Commercial trailers
- Tipper / plant trailers
- Boat trailers
- Car transporters
- Horse boxes

www.brenderup.com

08.2006

The New Brenderup Cargoliner Range

- Insulated and transparent roof to let light in. The light penetrates easily the roof which is insulated and prevents condensation (not relevant for model Cargo 2205/2260).
- Heavy duty chassis ensure durability and long lifetime. On trailers with 128 cm width, 3 members supports the floor, on trailers with 153 cm width the floor is supported by 4 members.
- Fitted with internal lashing eyes, making the load easy to secure (not relevant for model Cargo 2205/2260).
- Heavy duty door lock with integrated lock. (Only Cargoliner with doors)
- Rust free hinges ensure long lifetime.
- Low loading height, low centre of gravity and perfect road holding.



^{*)} Payload for trailers with doors - with ramp, see p. 6.

7205 B Technical data			
Total weight	1000	1300	kg
Payload*	635	929	kg
Int. length	205	205	cm
Int. width	128	128	cm
Int. height	150	150	cm
Wheels	R 13"	R 14"	

Choose between ramp or doors

- **Ramp**
Heavy duty ramp covered with an aluminium plate ensure easy loading with a sacktruck or boxes with wheels under.



Also available with 150 and 220 cm internal height.
^{*)} Payload for trailers with doors - with ramp, see p. 6.

7260 B Technical data			
Total weight	1000	1300	kg
Payload*	559	835	kg
Int. length	260	260	cm
Int. width	128	128	cm
Int. height	185	185	cm
Wheels	R 13"	R 14"	

Doors

The doors are easy to open and fix to the sites of the Cargoliner. It is easy to load/unload the trailer under windy weather conditions.



Also available with 150 and 220 cm internal height.
^{*)} Payload for trailers with doors - with ramp, see p. 6.

7260 B/TB Technical data					
Total weight	1300	1500	1600	2000	kg
Payload*	811	1011	1007	1407	kg
Int. length	260	260	260	260	cm
Int. width	153	153	153	153	cm
Int. height	185	185	185	185	cm
Wheels	R 14"	R 14"	R 14"	R 13"	

Durability and best driving abilities

Being fully enclosed the Cargoliner protects the load from wind, weather and theft.



7300 TB with sidemounted hatch.



^{*)} Payload with doors - payload with ramp see page 6. Several models, please see page 6.

7300 TB Technical data			
Total weight	2000	2500	kg
Payload*	1377	1823	kg
Int. length	300	300	cm
Int. width	153	153	cm
Int. height	185	185	cm
Wheels	R 13"	R 14"	



^{*)} Payload with doors - payload with ramp see page 6. Several models, please see page 6.

7300 TB Technical data			
Total weight	2500	kg	
Payload*	1779	kg	
Int. length	300	cm	
Int. width	153	cm	
Int. height	220	cm	
Wheels	R 14"		

Standard equipment Cargo 2205/2260:



Ground Support
The ground support is positioned under the platform and is activated with a handle.

Accessory for Cargo 2205/2260:



Tie down rings
Mounted in the bottom plate.

Standard equipment on the 7000 series:



Transparent roof
The light penetrates easily the roof which is insulated and prevents condensation.

Accessories for the 7000 series:




Prop stands
An indispensable accessory if the trailer is to be used as a workshop van (not relevant for model Cargo 2205/2260).



Ramp Extension
The ramp is equipped with an extension which unfolds when the ramp is let down.



Motorcycle kit
An ideal accessory when transporting motor bikes. The wheel support is mounted in the floor of the trailer. Also available for the 7000 series.



Lashing eyes
Fitted with internal lashing eyes, making the load easy to secure.



Brake lights
The stoplight is integrated in the rearframe of the trailer. A safety feature in heavy traffic and can be easily seen from long distance.



^{*)} Payload with doors - payload with ramp see page 6. Also available with 220 cm internal height.

7350 TB Technical data			
Total weight	2500	kg	
Payload*	1803	kg	
Int. length	350	cm	
Int. width	153	cm	
Int. height	185	cm	
Wheels	R 14"		